



# 2019 SiC 반도체 컨퍼런스

P-18

## Design and fabrication of 1.2kV 10A 4H-SiC Schottky barrier diodes with high current density

강인호<sup>a</sup>, 석오균, 문정현, 나문경, 김형우, 김상철, 방욱, 김남균

In Ho Kang<sup>a</sup>, Ogyu Seok, Jeong Hyun Moon, Moon Kyong Na, H. W. Kim, Sang Cheol Kim, Wook Bahng, Nam Kyun Kim

한국전기연구원

### Abstract:

In this work, we have designed and fabricated 1.2 kV 10A 4H-SiC Schottky barrier diodes (SBDs) with current density of 400A/cm<sup>2</sup> at the anode voltage ( $V_A$ ) of 2.6V and reverse leakage current of ~20uA at  $V_A$ =-1200V. To implement high current density, the epi-layer, the design parameters for active region including p-grid width and cell pitch, and field limiting ring space for edge termination were optimized by using analytic calculation and Silvaco<sup>TM</sup> simulator. Figures 1 shows the forward I-V curve of 1.2kV SBD. The forward voltage drop measured at the rating current of 10A is 1.9V. This value was obtained by on-wafer measurement and thus can be reduced by packaging chip. The current density at the forward voltage drop is 400A/cm<sup>2</sup>, which is higher than that of commercial product. Figure 2 shows the reverse I-V curve of 1.2kV SBD. The reverse leakage current at nominal blocking voltage of 1.2kV is about 20 uA, which is 5 times lower than that of commercial product. The detailed design procedures, explanation, and experimental results will be presented later.

### Keywords

4H-SiC, Schottky diode, high current density

### a. 교신저자 이메일

ihkang@keri.re.kr

---